



The TSM 15 is a multi-functional high-end loudspeaker. It has been optimised for use as a monitor, however the rotatable horn makes the TSM 15 equally suited to classic fullrange sound reinforcement applications, either vertically or horizontally mounted. A wide range of possibilities for mounting flying accessories and a discreet, modern design make the TSM 15 an interesting option for permanent installations. For applications requiring a longer throw, the TSM 15 can be fitted with a narrower horn with a coverage angle of  $60^{\circ} \times 50^{\circ}$ .

# **PRODUCT SPECIFICATIONS**

Speaker Components	15" Nd / 1,4" Nd
Description	Multi Purpose Sound System
Power AES / Peak	600 W / 1800 W
Impedance nominal	8 Ω
SPL 1 W / Peak @ 1 m	98 dB / 131 dB
Usable Range	45 Hz - 18 kHz (-6 dB)
Tuning Frequency excursion minimum	50 Hz
X - Overpoint acoustical	1,0 kHz
Coverage horizontal / vertical	90° x 60° - rotatable 60° x 50° - rotatable (optional)
Max. Splay Angle	
Connectors	2 x Neutrik Speakon NL4MP in/out Coding: 1 +/- HiMid, 2 +/- loop thru
Handles	2 x
Rigging / Fittings	3 x M10 / 6 x M8 35 mm pole mount
Weight	27 kg
Size height x width x depth	69,8 x 45,0 x 41,0 cm
Order No.	<b>00950/II/9060</b> (90° x 60°-version) <b>00950/II/6050</b> (60° x 50°-version)




The TSM 15 dp can be fitted with a narrower horn with a coverage angle of 60° x 50°.



The 35 mm threaded stand socket is integrated in the carrying handle.









# **Controller Setups** are available on our website:

http://www.seeburg.net/downloads.php




# Sensitivity 1 W @ 1 m + Impedance




# **COVERAGE PATTERNS**

2D Directivity Plot - horizontal



# 2D Directivity Plot - vertical





# Flying Bracket

for TSM 15 / A 8 / F 8 incl. screws (per unit: 2 pcs. M10 x 30 adjustable handle screws with axial bearing)

Order No. 01217/set



### Flying Bracket

for TSM 15 / A 8 horizontal alignment, incl. screws (per unit: 2 pcs. adapters, M10 hex lock nuts, flat- and rubber washers)

Order No. 01217/H/set



#### **Handle Screw**





### **Ergostyle Lobe Knob**

for flying brackets, M10 x20, with grip, adjustable

Order No. 08171



# Flange

for flying brackets,  $35 \text{ mm } \emptyset \rightarrow M10,$ 

Order No. 08126



# **Rubber Washer**

for flying brackets, 40 mm

Order No. 01205

# **Doughty Trigger Clamp**

for flying brackets, SWL 200 kg Order No. **01222** 



4 mm - 50 cm Order No. 01376



# **Chain Fastener**

VBS 7 mm Order No. 01378

# **Ring Screw**

M10- DIN 580, black zinced Order No. **73700** 

# **TV** Spigot

10 mm internal thread,  $28\;mm\;\varnothing$ 

Order No. 08128





A total of three M10 and six M8 flying points can be utilised for mounting the extensive accessories.



### **ACCESSORIES TSM 15**

### **Wall Mount**

for U-brackets, 40 kg max., incl. screws (M10 x 70 mm socket head screw, M10 hex lock nut and flat washer)

for 15" speakers Order No. 08130/F/400



with tilt unit, 40 kg max.

Order No. 08130



### **Speaker Stand**

Incl. wind up, 50 kg max., height 129 to 204 cm, K&M

Order No. 03011

50 kg max., K&M

Order No. 03010

# **Hexagon Grille**

for TSM 15 front grille version, for replacement, foam behind

Order No. 97075/hex/compl.



#### Cover

for TSM 15 / A 8, padded

Order No. **01240** 



#### **Rain Cover**

for TSM 15 / A 8,

Order No. 01240/outdoor



### Flight Case

for 2 pcs. TSM 15 / A 8 / A 8 Sub, heavy duty, 9,0 mm birch multiplex, PVC coated, 6 x recessed sprung handles, 4 x butterfly catches, 4 x 100 mm blue wheels, 2 pcs. with brake, interior lined with felt.

Order No. 16012/pro







Front grille version.



